	Document Title: Specification Sheet	Doc. No.:	QLC-GRP-SPEC-009
		Rev. No.	00
	Habilac	Effective Date:	MARCH 2024
		Page No.	1



Description: Organic rumen bypass (protected) fat that consists of calcium salts of selected fatty acids.

Ingredients: Calcium salts of long chain fatty acids (AAFCO Ingredient 33.14)

Applications: Supplemental fat for sustaining energy intake in high producing cows

Product Values:

<u>Property</u>	<u>Analysis Parameters</u>	<u>Method</u>	<u>Frequency</u>
Fat content, %	80 minimum	AOCS G 03-53	Production lot
Moisture and impurities, %	5.0 maximum	AOCS Da 2a-48	Production lot
Calcium, %	5 – 6	ASTM D 1126-92	
Granulometry		MI-090	Production lot
8 mesh (2.36 mm), %	30 maximum		
Fine particles (<500 µm), %	15 maximum		


(*) At time of packaging

Typical Fatty Acid Profile, % (AOCS Ce 1h-05)

Lauric (C12:0, saturated):	8.0 maximum
Myristic (C14:0, saturated):	3.5 maximum
Palmitic (C16:0, saturated):	40.0 – 50.0
Stearic (C18:0, saturated):	2.0 - 8.0
Oleic (C18:1 mono-unsaturated):	30.0 – 42.0
Linoleic (C18:2 poly-unsaturated):	6.0 - 20.0
Linolenic (C18:3 poly-unsaturated):	2.0 maximum

Country of Origin: Ecuador

Storage: Keep in a cool (between 16°C – 25°C/ 61°F – 77°F), dry area away from direct sources of light, heat, moisture, dust and pests. Avoid abrupt changes in temperature or humidity. Ensure proper product rotation.

	Document Title: Specification Sheet	Doc. No.:	QLC-GRP-SPEC-009
		Rev. No.:	00
<p style="text-align: center;">Habilac</p>		Effective Date:	MARCH 2024
		Page No.:	2

Packaging:	SAP Code
Bulk containers (big bags of 1MT)	100000300
Polyethylene bags of 25 kg	100000301

Shelf Life: 12 months in optimum storage conditions

Transportation: Transport in closed, clean containers away from any sources of contamination and direct heat.

CERTIFICATES



Information is furnished without warranty expressed or implied, except that it is accurate to the best knowledge of the Company and is based on information considered to be reliable. The Company makes no guarantee of results or performance of the product & assumes no responsibility for damages, as the conditions of handling and use are out of the Company's control.



USA: 357 McCaslin Blvd Suite 200, Louisville CO 80027 Phone: (720)-328-4558
 ECUADOR: Km 5½ Vía Manta-Montecristi, Ecuador. Tel: 593-52- 920-826. Fax: 593-52-924-252 – Casilla 13-05-4761